

Partial list of the 100+ supported applications

Design & Modeling

- AutoCAD
- Autodesk Inventor
- CATIA
- Google SketchUp
- Pro/ENGINEER
- NX
- Solid Edge
- SolidWorks

Digital Content Creation


- Autodesk 3ds Max
- Autodesk AliasStudio
- Autodesk Maya
- form•Z
- SOFTIMAGE|XSI

Visualization Tools


- Google Earth
- Autodesk DWF Viewer
- Autodesk Design Review
- SolidWorks eDrawings
- Dassault Systemes XML player
- 3Dconnexion Picture Viewer

Visit www.3dconnexion.com for a complete listing of supported applications.

Simply push, pull, twist and tilt the controller cap for responsive control.



Pan Right/Left



Pan Up/Down




Tilt



Spin



Roll



Zoom In/Out

Specifications

Navigation Control

Advanced 6 degrees-of-freedom optical sensor

Device speed

Adjustable to preference

Function Keys

15 programmable function keys

Interface type

USB or Serial (Serial supports UNIX/Linux only)

Weight (incl. Cable)

593g (USB) 619g (Serial)

Dimensions

194 x 139 x 58mm

EMC & safety

FCC, CE, VCCI, RRL, WHQL, CTICK, UL

System Requirements

- Intel Pentium 4/III or AMD/Athlon processor based system or greater
- Windows: 140 Megabytes free disk space for driver and plug-in installation
- UNIX/Linux: 2 Megabytes free disk space for driver installation
- USB 1.1 or 2.0

Operating Systems Supported

- Windows XP, x86 or x64
- UNIX (HP-UX 11, IBM AIX 5.2, Sun Solaris 8 or greater)
- Linux (Redhat Enterprise Linux WS 3, SuSE 9.0 or greater)

Americas

3Dconnexion, Inc.
San Jose, CA
P: 408 376 2500
F: 408 376 2525
E: info@3dconnexion.com

Europe/EMEA

3Dconnexion GmbH
Seefeld, Germany
P: +49 (0) 8152 9919 0
F: +49 (0) 8152 9919 50
E: info@3dconnexion.com

Japan

3Dconnexion
Tokyo, Japan
P: +81 (3) 3267 8490
F: +81 (3) 3267 8491
E: info@3dconnexion.com

