



SpacePilot™

Navigate Your 3D World™

Powerful functionality. Graceful styling.

SpacePilot is a true breakthrough in the world of user interface devices. Using SpacePilot together with a mouse engages both your hands in a natural, intuitive work style. One hand drives the SpacePilot, positioning your model, then rotating, panning and zooming in one single, fluid motion. Your mouse hand can simultaneously edit the model or select menu items.

50% fewer mouse clicks. 30% more productivity.

Adaptive sensing technology gives you the functionality you want, the instant you want it. Commands become available on the LCD and dynamically update when you switch applications or work modes within an application. Plus, an array of extendable, programmable speed keys—including Control, Fit and Modifier (Esc, Shift, Ctrl and Alt) and View—help you stay immersed in your design.

A virtual extension of your mind.

SpacePilot connects you to the 3D design process. Its optical sensors, finely-tuned springs and ergonomic design combine to deliver unprecedented control and fewer distractions.

Partial list of the 100+ supported applications

Design & Modeling

- AutoCAD
- Autodesk Inventor
- CATIA
- Google SketchUp
- Pro/ENGINEER
- NX
- Solid Edge
- SolidWorks

Digital Content Creation


- Autodesk 3ds Max
- Autodesk AliasStudio
- Autodesk Maya
- form•Z
- SOFTIMAGE|XSI

Visualization Tools


- Google Earth
- Autodesk DWF Viewer
- Autodesk Design Review
- SolidWorks eDrawings
- Dassault Systemes XML player
- 3Dconnexion Picture Viewer

Visit www.3dconnexion.com for a complete listing of supported applications.

Simply push, pull, twist and tilt the controller cap for responsive control.



Pan Right/Left



Pan Up/Down



Tilt



Spin



Roll



Zoom In/Out

Specifications

Motion controller

Advanced 6 degrees-of-freedom optical sensor

Device Speed

Adjustable to preference

Palmrest

Sculpted soft coat ergonomic form

Buttons

21+ Programmable speed keys, 15 reprogrammable

LCD

Viewing Area: (WxH) 4.0"x1.0" (102.4x30.2mm)

Active Area: (WxH) 3.7"x1.0" (93.4x26.2mm)

Display Format: 240x64

Interface type

USB

Weight

1.875 lb (0.85 kg)

Dimensions

(LxWxH) 9.3"x5.6"x2.0" (236 x143x53 mm)

Warranty

3 years

EMC & safety

FCC, CE, VCCI, RRL, WHQL, CTICK, UL

System Requirements

- Intel Pentium 4/III or AMD/Athlon processor based system or greater
- Windows: 140 Megabytes free disk space for driver and plug-in installation
- UNIX/Linux: 2 Megabytes free disk space for driver installation
- USB 1.1 or 2.0

Operating Systems Supported

- Windows XP, x86 or x64
- UNIX (HP-UX 11, IBM AIX 5.2, Sun Solaris 8 or greater)
- Linux (Redhat Enterprise Linux WS 3, SuSE 9.0 or greater)

Americas

3Dconnexion, Inc.
San Jose, CA
P: 408 376 2500
F: 408 376 2525
E: info@3dconnexion.com

Europe/EMEA

3Dconnexion GmbH
Seefeld, Germany
P: +49 (0) 8152 9919 0
F: +49 (0) 8152 9919 50
E: info@3dconnexion.com

Japan

3Dconnexion
Tokyo, Japan
P: +81 (3) 3267 8490
F: +81 (3) 3267 8491
E: info@3dconnexion.com

